






### Batch feed operation



For those who prefer the on/off switch built right into the disposer cover. InSinkErator offers the cover control accessory. It's just right for efficient batch feed operation. (Not available in all markets)

#### Dimensions (cm)



InSinkErator reserves the right to change product specifications without prior notice. The disposer described in this leaflet is for household use: usage in commercial situations is not covered by warranty.

# Evolution<sup>®</sup> 200

# **Category Benefits**

- Food waste is ground into particles and flushed away in seconds
- Clean, hygienic, convenient and • simple to use
- Easy method to manage food waste in the home, saving you time and helping to minimise trips to the outside dustbin
- Permanent in-house solution that is compact and sits under the sink without taking up valuable storage
- Easy to install into new or existing kitchens and can be fitted to most sinks
- Environmentally responsible, helping reduce the amount of waste that goes to landfill sites

# Features

- Evolution ultra-guiet technology
- . Evolution 3-stage grind technology
- Auto-reverse grinding action
- High-torque Dura-Drive™ induction motor
- Built-in air switch with chrome button
- 6 Year guarantee
- Stainless steel grind elements and grind chamber
- Overload protection
- Quick Lock® mounting assembly for faster, easier installation

## Sample Specification

Food waste disposer(s) shall be InSinkErator<sup>®</sup> Model Evolution 200 with 3-stage grind and ultra-guiet technologies, 1 hp (110-120V) or .75 hp (220-240V) motor, auto-reverse grind system, stainless steel grind chamber, grinding elements and built-in air switch in chrome.

Guarantee: 6 Year parts and service.

The complete InSinkErator guarantee is included in the Care & Use Booklet packed with each unit.

## Specifications

Continuous	Sound Technology	Anti-Vibration Mounting
Wall Switch or Built-In Air Switch		and Tailpipe Quiet Sink Baffle
Single Phase		Multi-Layer Sound
Auto-Reverse Grind System		Insulation Premium Stainless
Intermittent		Steel Stopper
Lubrication Permanently Lubricated Upper & Lower Bearings	Grind Chamber Capacity	1180 ml
	Motor Protection	Manual Reset Overload
11.4 kg	Average Water Usage	Approximately 4.0 L per Person per Day
Stainless Steel Light Gray	Average Electrical Usage	3-4 KWH per Annum
33.0 cm	Drain Connection	1-1/2" (3.81 cm)
3-Stage Grind Technology		Anti-Vibration
Jam Preventing Circuit	cuit	(Hose Clamp)
	Dishwasher Drain Connection	Yes
	Wall Switch or Built-In Air SwitchSingle PhaseAuto-Reverse Grind SystemIntermittentPermanently Lubricated Upper & Lower Bearings11.4 kgStainless Steel Light Gray33.0 cm	Wall Switch or Built-In Air SwitchTechnologySingle Phase-Auto-Reverse Grind System-Intermittent-Permanently Lubricated Upper & Lower BearingsGrind Chamber Capacity11.4 kg-Stainless Steel Light Gray-Stage Grind Technology Jam Preventing Circuit-Dishwasher Drain

Volts/Hz	HP	Average Load
120V, 60 Hz	1.0	10.2 A
220-240V, 50-60 Hz	.75 (@240V/50Hz)	370 W

InSinkErator Division Emerson Electric Co. 4700 21st Street Racine, WI 53406-5093 USA Sales/Service Tel: 262-554-3652 www.insinkerator.com/worldmap.html



The Emerson logo is a trademark and a service mark of Emerson Electric Co. The mounting collar configuration is a trademark of Emerson Electric Co. INSinkErator may make improvements and/or changes in the specifications at any time, in its sole discretion, without notice or obligation and further reserves the right to change or discontinue models. ©2016 InSinkErator, a business unit of Emerson Electric Co. All Rights Reserved.